



MATERIALS

Housing: PBT, UL 94V-0, Color: Ivory.
Bracket: PA66, UL 94V-0, Color: Ivory.
Terminal: Copper Alloy.
Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Area.
Shell: Zinc Alloy with Nickel Plating
Boardlock: Steel with Tin Plating
Rivet: Copper Alloy with Nickel Plating
Contact: Brass

ELECTRICAL

Voltage Rating: 40V AC(r.m.s.)
Current Rating: 3A
Contact Resistance: <20 mΩ
Insulation Resistance: >1000 MΩ
Dielectric Withstanding Voltage: 500V AC
Operating Temperature -40°C to +85°C
Mating cycles: 100

RoHS Compliant

PLATING:
6: Selective Gold Flash/50u" Ni (STD)
7: Selective 15u" Gold/50u" Ni
8: Selective 30u" Gold/50u" Ni

DVIR-29SXW-X

Accessories
N = w/out screws
J = loose screws
A = fix screws

OST ON-SHORE TECHNOLOGY, INC.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

TITLE		DVI Series - 29 Contacts (24+4+1) female Right/ Angle Integrated			
PART NO.	DVIR-29SXW-X	DWG NO.	DVIR-29SXW-X.DWG		
APPROVED	CHECKED	DESIGNED	DRAWN	4050	
		Tony 2006.11.24	Steven 2006.11.24	Tolerance	
				UNIT: mm/in	.X ± 0.30/.012
				SCALE: NONE	.XX ± 0.20/.008
				SHEET: 01/02	.XXX ± 0.10/.004
				REV.: B	

